

スタンダード100 世界トップレベルの安全な繊維製品の証 最も厳しい品質基準である製品分類 I の認証を 取得しております。



STANDARD 100

N-KEN 12133 Nissenken





Recycling Material PA 💽 NC-932

col: 01·09·28·40·41·42·45·46·48·58·64·95 size: 13·15·19·21·23·25·28mm



NC-1030 (PA) col: 01.09.28.40.41.42 45.46.48.58.64.95 size: 11.5.13.15.18.20.23 25.28mm







NC-35



48

PA (E)



NC-933

PA (S)

48

NC-1005 (PA)

col: 46·48·09 size: 15·18·20·23·25mm





NC-1010 (PA)

col: 46·48·09 size: 15·18·20·23·25mm



CK-800

col: 46 · 48 · 09 size: 15.18.20.23.25mm

NC-1040 (PA)





CK-306 (ABS) (C)

ABS ABS PA col : 42·46·48·09 ABS col : WG·AG size: 13.15.18.21.23mm

CK-401



CK-700

col: 42·46·48·09 size: 15·18·20·23mm





NC-934



48





PA col : 46 · 48 · 09 ABS col : AG · AS size: 15.18.21.23mm



DNC-2410 (PA) (S)











64/KN



48/S

46



09/KN

AS/48

BC-100 (PA) (€) (PE)





col: 01·09·28·40·41·42·45·46·48·58·64·95 size: 20·25·30·40·45·50mm

※ ピン付きでの販売もしております。 ご希望される場合は指示してください。 PIN col: S·A/G·K/N (MB) (検針器対応)



Recycling Material











※ ピン付きでの販売もしております。 ご希望される場合は指示してください。 PIN col: S·A/G·K/N (MB) (検針器対応)





20 mm



col: 042.044.049.009 size: 15.18.20.24mm





心地よい感触の表現(しつとり感)(ぬめり感)の追及















M-2012 (PA) (EX) (PEX) col: M041·M046·M048·M064·M009 size: 25·30·50mm

※ ピン付きでの販売もしております。 ご希望される場合は指示してください。 PIN col: S·A/G·K/N (MB) (検針器対応)





M048




















M048







M041



M064



M046





50 mm